

Antivibration Gel Stainless Steel Studs

Both Ends Threaded Studs / Threaded Stud, Plate Mount / Antivibration Gel Bushings / Sheets / Rubber Covered Type

■Silicone vibration absorber with longer fatigue life than rubber products. Suitable for light load and micro-vibration.

Both Ends Threaded Studs




RoHS10


* Slots are added to prevent rotation when tightening. Hold it with a flathead screwdriver, etc.
❗Slot is not available for Ultra-Light Type.

Ultra-Light Type

BGELA (Standard Type)
SBGELA (Lower Thread Short Type)
WBGELA (Short Type)
TBGELA (Upper Thread Short Type)





Threaded Stud Dimension





Lightweight Type

BGELM (Standard Type)
SBGELM (Lower Thread Short Type)
WBGELM (Short Type)




Medium Load Type

BGELH (Standard Type)
SBGELH (Lower Thread Short Type)
WBGELH (Short Type)
TBGELH (Upper Thread Short Type)




■Material
Main Body: Silicone
Attaching Portion: SUS304 Equivalent
❗Accessory:
Hex Nut: SUS304 Equivalent
Spring Washer 2 pcs. each:
SUS304 Equivalent

Type	Part Number	No.	D1	D2	H1	H2	ℓ	ℓ1	M
Ultra-Light	BGELA	006	18	12	13	9	15	10	4
	SBGELA	014	25	20	18	14	20	14	6
	WBGELA	030							
	TBGELA	050							
Lightweight	BGELM	070	30	24	22	18	18	14	6
	SBGELM	071*							
	WBGELM	100							
	TBGELM	101*							
Medium Load	BGELH	150	35	28	25	21	17	12	6
	SBGELH	151*							



Type	Part Number	No.	Working Load N (kgf)	Spring Constant N/mm (kgf/mm) ± 20%	Hardness Asker C Penetration	Frequency Used Hz	Body Color	Unit Price
Ultra-Light	BGELA	006	4.9~7.84 (0.5~0.8)	6.17 (0.63)	-	64.7	23~	① Milky White
	SBGELA	014	7.84~19.6 (0.8~2.0)	9.31 (0.95)	-	60.7	20~	② Milky White
	WBGELA	030	19.6~34.3 (2.0~3.5)	13.13 (1.34)	19.7	32.0	17~	③ Milky White
	TBGELA	050	34.3~63.7 (3.5~5.5)	21.75 (2.22)	29.8	-	16~	④ Light Green
Lightweight	BGELM	070	63.7~88.2 (5.5~8.5)	33.71 (3.44)	38.0	-	16~	⑤ Light Orange
	SBGELM	071*						
	WBGELM	100	88.2~122.5 (8.5~12.5)	46.74 (4.77)	44.3	-	16~	⑥ Light Blue
	TBGELM	101*						
Medium Load	BGELH	150	122.5~245.1 (12.5~25.0)	56.2 (5.74)	52.5	-	14~	⑦ Milky White
	SBGELH	151*						





■Silicone vibration absorber with longer fatigue life than rubber products. Suitable for light load and micro-vibration.

Threaded Stud, Plate Mount



RoHS10

BGELP




* Slots are added to prevent rotation when tightening. Hold it with a flathead screwdriver, etc.
❗Slot is not available for 006 and 014.

■Material
Main Body: Silicone
Attaching Portion: SUS304 Equivalent
❗Accessory:
Hex Nut: SUS304 Equivalent
Spring Washer 1 pc. each:
SUS304 Equivalent

Part Number	Type	No.	D1	D2	H1	H2	t	ℓ	M
BGELP		006	12	18	12	11	2	15	4
		014	20	25	17	16	2	20	6
		020							
		050	24	30	22	21	2	18	6
BGELP		100							
		006							
		014							
		020							
BGELP		050							
		100							
		006							
		014							

Vibration Transmissibility Data



❗Hardness: Listed values are not guaranteed values but an example of measured values. ❗Penetration: JIS K2207, Asker C: JIS S6050 See P391 kgf=Nx0.101972



Antivibration Gel Bushings




RoHS10

■Features: The penetrating bolt of Antivibration Gel Bushing can minimize horizontal misalignment.

GELB



■Material Main Body: Silicone
Collar: SUS304 Equivalent




❗Tighten the bolt until it touches the collar.
❗Accessory: Washer, Low Head Bolt: SUS304 Equivalent
Hex Nut: SUS304 Equivalent

Part Number		D1	D2	d1	d2	H1	H2	L	t	Working Load N (kgf)	Spring Constant N/mm (kgf/mm) ±20%	Hardness		Frequency Used Hz	Included Washer O.D.	Included Bolt Size	Body Color	Unit Price
Type	No.											Asker C	Penetration					
GELB	1101	11	7	4	3	3	3.5	6	0.5	0.49~1.77 (0.05~0.18)	10.59 (1.08)	-	80	At 0.05kg: 90 ~ At 0.18kg: 60 ~	Ø12	M3x15	Milky White	
	1401	14	9	5	3	4	4	7	1	1.18~6.08 (0.12~0.62)	26.18 (2.67)	-	50	At 0.12kg: 95 ~ At 0.62kg: 50 ~	Ø15	M3x15	Milky White	
	1402									6.08~9.81 (0.62~1.00)	56.68 (5.78)	30	-	At 0.62kg: 70 ~ At 1.00kg: 55 ~			Light Green	
	2501	25	14	6	4	5	6.5	11	1	9.81~36.77 (1.00~3.75)	86.59 (8.83)	30	-	At 1.00kg: 70 ~ At 3.75kg: 35 ~	Ø25	M4x20	Milky White	
	2502									36.77~78.45 (3.75~8.00)	170.15 (17.35)	50	-	At 3.75kg: 40 ~ At 8.00kg: 25 ~			Light Green	

❗Recommended frequency varies depending on the condition of load. ❗Penetration: JIS K2207, Asker C: JIS S6050 See P391 kgf=Nx0.101972

Vibration Transmissibility Data






Antivibration Gel Rubber Covered Type



RoHS10


HBGELP




■Material
Main Body: Silicone
Coating: EPDM Synthetic Rubber
Attaching Portion: SUS304 Equivalent
❗Accessory:
Hex Nut: SUS304 Equivalent
Spring Washer: SUS304 Equivalent
1 pc. each

Part Number	Type	No.	Working Load N (kgf)	Frequency Used Hz	Unit Price
HBGELP		300	245.1~343.2 (25.0~35.0)	13~	

■Features
-Low frequency vibration absorbing gel with working load limit of 25 ~ 35 kgf (when 1pc. is used) and lowest usable frequency of 13Hz.
-Silicone gel used for the main body is ethylene rubber covered, and has good environmental resistance. Outdoor use is possible.




Vibration Transmissibility Data



■Silicone vibration absorber with longer fatigue life than rubber products. Suitable for light load and micro-vibration.


Antivibration Gel Sheets



RoHS10

Type	Material	Hardness
No Adhesive	Silicone	Asker C
Adhesive	Silicone	Penetration
BGEPG		55
BGEPGA		30
BGPEPM		
BGPEPMA		

❗The values of hardness are reference values.




Ordering Example
Part Number
BGEPG50

Type	No Adhesive	Adhesive	A	a	Proper Load N (kgf)	Deflection Characteristic N/mm (kgf/mm)	Frequency Used Hz	Protrusion	Color	Unit Price
BGEPG		BGEPGA	50	7	19.6~49 (2~5)	22 (2.25)	40~	4x4=16 pcs.	Milky White	
		BGEPMA			49~294 (5~30)	93 (9.5)		8x8=64 pcs.	Light Green	
		BGEPGA	100	8	98~196 (10~20)	98 (10)			Milky White	
		BGEPMA			196~1225 (10~125)	431 (44)			Light Green	


kgf=Nx0.101972

❗Can be cut with a utility knife between protrusions.
❗Adhesive Type has an operating temperature between -40 and 100°C.
❗Reference: Adhesive Strength (180° Peeling Strength) 14.5N/25mm Width (When affixed to SUS304)
❗As pressure sensitive adhesive is used, be sure to apply sufficient pressure so that the joint sections may firmly adhere to each other.
❗Adhesive Type uses 75µm PET film base material. ❗Oil may ooze out to the backing paper.

Vibration Transmissibility Data



Load Deflection Data




Example

■Features of Antivibration Gel Bushings and Antivibration Gels
-Effective for light loads and minute vibrations that are difficult for antivibration rubbers to absorb.
-Excels in durability.
-There are no secondary and tertiary resonances that hinder the antivibration effects.

How to Mount

-Attach so that load is applied evenly.
-Antivibration Gel products are to be used for vertically oriented loads only. Install BGELP and BGELA bushings with the small diameter ends facing up.
-Shifted or twisted installation drastically lowers performance and durability.
-Do not use in tension.



Cautions

-The height becomes lower due to being compressed when loaded.
-Do not remove the rubber burrs around the studs as the burrs prevent separations of studs and antivibration materials.
-Antivibration Gel and Rubber are designed to be used in compression.